

CRYOG



WATER-REPELLENT CRYOGENIC LEATHER GLOVE

Ref. CRYOG



Product specifications

Water-repellent cowhide full grain leather. Aluminized polyester insert. Cowhide split leather cuff. Hand and cuff in synthetic. American assembly. 20 cm cuff. Length: 40 cm.

Full grain waterproof treated cowhide (TECHNICUIR).

Thickness of between 1.1 and 1.3 cm.

Insert aluminised polyester.

Synthetic lining.

Split cowhide leather cuff.

Kevlar® Technology sewn.

COLOUR

Straw-coloured

SIZE

10

Product Use - Risks



Cold / Weather



Wearing



Heavy industry

Product's highlights & user's benefits



Water repellent leather

Good splash protection



Velcro tape

Adjustable fit



Aluminised polyester

Thermal protection



Tested with liquid nitrogen using method MR019

Work in all safety up to -196°C (a few seconds)

Superior quality

Increased lifespan
Comfortable to wear
Flexibility

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

2: Dexterity (from 1 to 5)

4/4 >180 mn: Waterproofing : Ability of the glove to withstand the penetration of water, moisture.

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

2: Resistance to abrasion (from 1 to 4)

2: Resistance to cutting (from 1 to 5)

2: Resistance to tear (from 1 to 4)

2: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN511:2006 Protective gloves against cold (X = Unrealized test)

2: Resistance to convective cold (from 1 to 4)

3: Resistance to contact cold (from 1 to 4)

X: Waterproof (0 or 1)



EN420:2003+A1:2009 4.2 Glove - Resistance to water penetration

4/4 ≥ 180 mn: Level of performance - Time of penetration

References

References	Bar code	COLOUR	SIZE		
CRYOG10	3295249026844	Straw-coloured	10	36	6