FIREMAN SABF RAC2 Boots



Colors

Black





ATS sole (registered design)

Antiperforation + Safety toe cap

Polymer toe cap*

Composite anti-perforation mid-sole*

Outside height (size 8): 330 mm

Weight (size 8): 2100g / pair Elastomer: fireproofed NBR / CR

(fireproofed nitrile/polychloroprene rubber)

Reference: FIREMAN SABF RAC2 Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals: fuels, oils, weak and diluted acids, solvents. Excellent resistance to abrasion and cuts

Comply with standards:

EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

EN ISO 20345 S5 HRO SRC

- · Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

EN 13832-3 J P Q

- Boots highly resistant to chemicals:
- N-Heptane (J)
- Hydrogen peroxide (P)
- Isopropanol (Q)

EN 13287

- Sole slip resistance (SRC):
- · Steel floor.
- · Ceramic floor.

Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9		10 ½	11 ½	13	14

Please contact us for sizes 3 and 4.5 certificate.

^{*} Sizes 3 and 4.5 have steel too cap and steel midsole.