



Compact 150 Regular

The Compact 150 Mark II is ideal for general heavy use professional and commercial applications due to its high abrasion resistance outer cover.



COMPACT 150 REGULAR

3MV1

KEY FEATURES

- High abrasion resistance fabric
- Quick burst zip fastening cover
- Quick release buckle
- Detachable crutch strap
- Inflation system operational readiness indicator window on the back.
- Service date information window on the back

INFLATABLE BLADDER

- Single chamber
- Oral inflation tube
- SOLAS approved retro-reflective tape on bladder
- Red recovery grab strap on bladder marked "LIFT"
- 38g CO₂ gas cylinder
- Inflation system
- Whistle

ACTUAL BUOYANCY

- 172N

AVAILABLE SIZES

- Universal

COLOUR

- RS0 Red
- AS0 Olive Green
- BS0 Blue

CERTIFIED

- EN ISO 12402-3 : 2006 +A1 : 2010
- CE

3MV1E6N15: *United moulders DPI inflator*

3MV1E5N15: **** MEC015 ****

MULLION BELGIUM

Export office
Fabriekstraat 23
8850 Ardooie
BELGIUM
T +32 (0)51 74 15 02
F +32 (0)51 74 09 63
info@mullion-pfd.com

MULLION UK

2 Hebden Road
UK-Scunthorpe
North Lincolnshire DN 15 8DT
T +32 (0)51 740 830
F +32 (0)51 740 963
unitedkingdom@mullion-pfd.com

MULLION IRELAND

Cweedore Business Park
Derrybeg, Co. Donegal
IRELAND
T +353 (0)74 95 31 169
F +353 (0)74 95 31 591
ireland@mullion-pfd.com



Discover
our products

© 2017 Mullion Survival Technology Ltd - Maritime Safety Suits & Lifejackets

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.