

# Technische fiche / Fiche technique / Technical sheet



## 3715Z0

Right Angle Light

Peli leads the way yet again with the 3715Z0 right angle light. Featuring downcast LEDs for illuminating your path, the 3715Z0 LED light also features 189 lumens (high) and 90 lumens (low), and a flashing mode. Another first is a built in battery life indicator so you will know your light's battery level before you go in. Compact, rugged, and lightweight, the 3715Z0 LED light contains the latest technology, Peli's legendary build quality and lifetime guarantee of excellence. Certified to ATEX Zone 0 (Category 1).

The 3715Z0 LED - Now you can **WATCH YOUR STEP**.



### DIMENSIONS

**Length** 5.36" (13.6 cm)

### MATERIALS

**Body** Anti-static Impact Modified PC/PBT  
**O-Ring** Buna-N  
**Lens** Anti-static PMMA  
**Shroud** Anti-static Impact Modified PC/PBT  
**Clip** Anti-static Impact Modified PC/PBT

### COLOURS

■ High Visibility Yellow

### LIGHT SPECS

**Lamp Type** LED  
**Lamp Secondary Type** LED

### POWER

**Battery Size** AA  
**Battery Type** Alkaline  
**Battery Quantity** 4  
**Battery Level Indicator** 3 Blue LEDs  
**Volts** 6.0v

### WEIGHT

**Weight With Batteries** 14.4 oz (408 gr)  
**Weight Without Batteries** 11.0 oz (312 gr)

## SWITCH






<b>Switch Type</b>	Push Button
<b>Light Modes</b>	High / Low / Downcast / Flashing

## CERTIFICATIONS

**ATEX Zone 0**

## OTHER

**Minimum Pack** 1

<b>FL1 STANDARD</b>	<b>HIGH</b>	<b>LOW</b>	<b>DOWNCAST</b>
	189 LUMENS	90 LUMENS	23 LUMENS
	4h 0mins	7h 0mins	31h 0mins
	249m	157m	24m
	15552cd	6150cd	150cd
	IPX4		

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 01-22-21