Technische fiche / Fiche technique / Technical sheet

BLS 200 SERIES FILTERS WITH BAYONET CONNECTION

With features such as high efficiency, ease of use and safety the filters series are the best offered by BLS, protecting from gases and vapours as well as toxic particulates. They are highly efficient, easy to use and highly secure.



RESPIRATORY PROTECTION

b-lock

PRODUCTS

ACTIVATED CARBONS

The quality of the activated carbons used by BLS for the filtration of gases and vapours, meets high standards of safety ensuring excellent filtration performances. They are produced without toxic additives such as Hexavalent Chromium (Cr VI).

b-lock BAYONET CONNECTION

This connection is highly intuitive allowing a quick and safe hold on the mask. It has a locking feedback allowing the user to know if the filter has been properly placed.



DUST FILTER

Filtering efficiency is 99,99%. The integrity of the filtering material is ensured by a protective mesh.



TESTED ON FORMALDEHYDE

Specific tests show that ABEK and ABE special BLS carbons are capable to guarantee protection from formaldehyde. Even with class 1 filters it's possible to achieve proper protection. At the end of the test the detected concentration of formaldehyde at the end of the filter is lower than half the Threshold Limit Value according to NIOSH TEB-APR-STP-0039A (Breakthrough Point).

FILTER CANISTER

Made of non deformable ABS allows to have a absolute control over the compression of the activated carbon grains within, this way air corridors are completely avoided making the filter 100% safe.

Safety Shop.be

Westkaai 7 - B2170 Merksem / Antwerpen Tel. 03 646 99 60 - Fax 03 646 00 25 info@safetyshop.be - www.safetyshop.be

P 1/3



BLS 200 SERIES FILTERS WITH BAYONET CONNECTION

RESPIRATORY

PROTECTION

PRODUCTS

BLS SRL via dei Giovi, 41 20032 Cormano (MI) - Ítaly t/f +39 0239310212 / 0266200473 info@blsgroup.it - www.blsgroup.com



MATERIALS

FILTER'S CANISTER DUST FILTERING MATERIAL GASES AND VAPOURS FILTERING MATERIAL

Acrylonitrile butadiene styrene (ABS) Pleated fiber mesh Activated carbons grains

STORAGE

SHELF-LIFE 5 years TEMPERATURE RELATIVE HUMIDITY 80% max

-10°C/+50°C

TECHNICAL DATA

| MODEL | PROTECTION | ТҮРЕ | TESTED on Formaldehyde | TESTED on Fluoridric Acid | NPF (half masks) | NPF (full face masks) | CONNECTION |
|----------|------------|---------------|---------------------------|------------------------------|------------------|--------------------------|------------------|
| BLS 202 | P3 R | Dust | _ | _ | 48*TLV | 1000*TLV | Bayonet (b-lock) |
| BLS 211 | A2 | Gases&vapours | _ | - | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 212 | AX | Gases&vapours | _ | - | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 213 | ABE1 | Gases&vapours | _ | - | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 214 | ABEK1 | Gases&vapours | _ | - | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 221 | A2P3 R | Combined | _ | - | 48*TLV | 1000*TLV | Bayonet (b-lock) |
| BLS 222 | ABEK1P3 R | Combined | - | \checkmark | 48*TLV | 1000*TLV | Bayonet (b-lock) |
| BLS 225 | AXP3 NR | Combined | _ | _ | 48*TLV | 1000*TLV | Bayonet (b-lock) |
| BLS 226 | ABE1P3 R | Combined | _ | _ | 48*TLV | 1000*TLV | Bayonet (b-lock) |
| BLS 242 | ABE2 | Gases&vapours | \checkmark | - | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 243 | ABEK2 | Gases&vapours | \checkmark | - | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 244 | K2 | Gases&vapours | _ | _ | 50*TLV | 2000*TLV | Bayonet (b-lock) |
| BLS 253* | ABE2P3 R | Combined | _ | - | 48*TLV | 1000*TLV | Bayonet (b-lock) |
| BLS 254* | ABEK2P3 R | Combined | _ | _ | 48*TLV | 1000*TLV | Bayonet (b-lock) |

(TLV) Threshold Limit Value (NPF) Nominal Protection Factor

* this filters cannot be used with half masks because their weight combined is more than 300g A = Organic gases and vapours AX = Organic gases and vapours (Boiling point <65 ° C) E = Acid gases and vapours K = Ammonia and derivatives P = DustsB = Inorganic gases and vapours

CERTIFICATION

BLS filters are:

Certified according to European Regulation 2016/425 (Personal Protective Equipments)

• Certified as PPE of III category, in presumption of conformity to harmonized standard EN 143:2000 + A1:2006 and EN 14387:2004 + A1:2008

• Certified and controlled according to Annex D by Italcert S.r.I. (Notified Body n°0426)

• CE marked

BLS management system is ISO 9001 certified

BLS 200 SERIES FILTERS WITH BAYONET CONNECTION







TYPES OF FILTERS







Dust

Gases&vapours

Combined



Half masks BLS 4000 next S -BLS 4000 next R



COMPATIBLE DEVICES

Full face masks BLS 5700 - BLS 5600

TRANSPORT

| MODEL | CODE | PROTECTION | WEIGHT (g) ± 3 | Q.TY/BOX | Q.TY/CARTON | CARTON WEIGHT (Kg) ± 0,1 |
|---------|---------|------------|----------------|----------|-------------|--------------------------|
| BLS 202 | 8011118 | P3 R | 67 | 8 | 64 | 5,9 |
| BLS 211 | 8011109 | A2 | 89 | 8 | 64 | 7,3 |
| BLS 212 | 8011205 | AX | 111 | 8 | 64 | 5,7 |
| BLS 213 | 8011110 | ABE1 | 100 | 8 | 64 | 7,8 |
| BLS 214 | 8011111 | ABEK1 | 106 | 8 | 64 | 8,3 |
| BLS 221 | 8011112 | A2P3 R | 135 | 8 | 64 | 10,4 |
| BLS 222 | 8011113 | ABEK1P3 R | 151 | 8 | 64 | 11,5 |
| BLS 225 | 8011206 | AXP3 NR | 157 | 4 | 32 | 6,6 |
| BLS 226 | 8011145 | ABE1P3 R | 139 | 8 | 64 | 10,7 |
| BLS 242 | 8011133 | ABE2 | 125 | 8 | 64 | 10,0 |
| BLS 243 | 8011114 | ABEK2 | 139 | 8 | 64 | 10,5 |
| BLS 244 | 8011134 | К2 | 142 | 8 | 64 | 10,5 |
| BLS 253 | 8011140 | ABE2P3 R | 175 | 4 | 32 | 6,8 |
| BLS 254 | 8011141 | ABEK2P3 R | 180 | 4 | 32 | 7,4 |

IMPORTANT

BLS declines any responsibility, direct or indirect, from any misuse of both devices and instructions. User is responsible for the determination of product compliance with the intended use.

SELECTION GUIDE

CLASS

- Determines the duration of the filter:
- Class 1 = 1000 ppm, Class 2 = 5000 ppm

COLOUR CODES

- A = Organic gases and vapours
- AX = Organic gases and vapours (Boiling point <65 ° C)
- B = Inorganic gases and vapours
 - E = Acid gases and vapours
- K = Ammonia and derivatives
- \square P = Dusts