

FIREMAN SABF Boots



Colors

Black



ATS sole
(registered
design)



Anti-
perforation +
Safety toe cap

Polymer toe cap*

Composite anti-perforation
mid-sole*

Outside height (size 8): 370
mm

Weight (size 8): 2100g / pair

Elastomer: fireproofed NBR /
CR

(fireproofed
nitrile/polychloroprene
rubber)

Reference: FIREMAN SABF Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents.

Excellent resistance to abrasion and cuts

Used with chemical protective suits (satisfy permeation tests according to EN 943-1 and EN 943-2).

Comply with standards :

EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

EN ISO 20345 S5 HRO SRC

- Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

EN 13832-3 J P Q

- Boots highly resistant to chemicals :
- N-Heptane (J)
- Hydrogen peroxide (P)
- Isopropanol (Q)

EN 13287

- Sole slip resistance (SRC) :
- Steel floor.
- Ceramic floor.

Marine fire protection equipment certified by SEE-BG, notified body N°0736 .

* Sizes 3 and 4.5 have steel toe cap and steel midsole.

Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14

Please contact us for sizes 3 and 4.5 certificate.