Europe / Africa Partners Where To Buy



PRODUCT NUMBER: 2232533

Tuff Cut Nit

Handling of heavy parts with high cut risks in oily and/or greasy environment. Light heat protection (up to 100°C)

Honeywell

Q

Overview

Reference Number

2232533

Product Type

Gloves

Range

Cut and Puncture Protection

Line

Cut resistant

Brand

Honeywell

Brand formerly known as

SPERIAN

Industry

- Industry Automotive and Part Manufacturer Aviation Building and Construction
- General Industry Iron and steel industry Logistics Metal steel Minning and Quarrying
- Offshore Paper Industries Ship Building

Product Use

Handling of heavy parts with high cut risks in oily and/or greasy environment. Light heat protection (up to 100°C)

Features & Benefits

Feature

Knitted glove in Kevlar, high tenacity polyamide, steel fiber.

Benefit

COMFORT

The knitting technique helps to obtain a glove that conforms snugly to the hand and good dexterity. The glove offers maximum comfort and added sturdiness.

The Kevlar fibre ensures good comfort in contact with the hand. The use of foam Nitrile makes the glove more flexible than standard nitrile.

RESISTANCE

Tuff Cut Nit - 2232533

The composition of the glove offers outstanding cutting resistance (level 5).

The Nitrile foam coating brings good resistance and good grip to oil and grease. The 3/4 coating increase the protection to oil

HYGIENE

Its colour make it more soilproof, thus ensuring a longer last.

Feature

Plated Kevlar inside

Benefit

Offer a greater comfort and avoid the contact of the steel fiber with the skin

Feature

Black nitrile foam coating

Benefit

The Nitrile foam coating brings good resistance and good grip with oil and grease.

The use of foam Nitrile makes the glove more flexible than standard nitrile.

Technical Description

Description

CE CATEGORY : II Intermediary risks In accordance with standards : EN 420-2003 EEC Basic standards EN 388-2016 Mechanical Hazards EN407-2004 : Thermal risks

CHARACTERISTICS:

Knitted glove in Kevlar, high tenacity polyamide, steel fiber.

Black nitrile foam coating

Product Technology

Knitted

Fiber

Kevlar, polyamide high tenacity, steel fiber

Gauge

10

Glove/liner color

Yellow / Black

Coating Type

Nitrile foam

Coating Color

Black

Length

30 cm

Harmlessness

In conformity with the European Standards

Dexterity

Class 5

Sizes

7 to 11

EN 407 - Heat and/or Fire

Behaviour and/or fire	X
Resistance to contact heat	1
Resistance to convective heat	X
Resistance to radiant heat	X
Resistance to small metal splashes	X
Resistance to molten metal splashes	X

Tuff Cut Nit - 2232533

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	X
Tear resistance	4
Puncture resistance	3
Cutting resistance (TDM test)	D

ASTM F1790-97

ANSI Level Cut Resistance	ISO 13997 : 30 N
---------------------------	------------------

Additional Information

User Manual

UI 206

Maintenance

Storage Information

Minimum packaging 10 pairs.

Cartons of 100 pairs.

Care Instructions

This article can be cleaned. For cleaning instructions please contact Honeywell safety products

© Honeywell International Inc.