

Technische fiche / Fiche technique / Technical sheet



2460Z1 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses a long-life NiMH battery pack cat # 2479 for extended run time. It comes with a charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



DIMENSIONS

Length 7.00" (17.8 cm)

MATERIALS

Body Anti-static Impact Modified PC/PBT
O-Ring Ethylene Propylene
Lens Polycarbonate (PC)
Shroud Anti-static Impact Modified PC/PBT
Contact Spring Retainer Stainless Steel / Phosphore Bronze

COLOURS

■ High Visibility Yellow

LIGHT SPECS

Lamp Type LED

POWER

Battery Size AA
Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 5 hrs
Volts 4.8v

WEIGHT

Weight With Batteries 7.8 oz (221 gr)
Weight Without Batteries 4.4 oz (125 gr)
Packaged Weight 1.4 oz (40 gr)

SWITCH

Switch Type One-handed Safety Switch

Light Modes






On / Off

CERTIFICATIONS

ATEX Zone 1

OTHER

Minimum Pack 1
Military yes
Package Code C

FL1 STANDARD	HIGH
	181 LUMENS
	5h 0mins
	181m
	8235cd
	IPX7

ACCESSORIES



2468Z1
220V Adapter



0770
Helmet Light Holder



2480F
Deck/Dash Charger Base Unit



2469P
Replacement Battery

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-19-21