



3325Z0

Peli 3325Z0 Multi-Talented LED Torch: Compact, lightweight, Back Switch and ATEX Zone 0 Certified

The Peli 3325Z0 is compact, ATEX Zone 0 certified and with a button back switch for one hand activation. It uses 3 AA alkaline batteries, produces 155 lumens of powerful light, weighs only 173 gr (including batteries) and is 15.4 cm long. Being certified to ATEX Zone 0 (Cat. 1) means that it can be used in the most hazardous work environments.

The back mounted switch makes the 3325Z0 a perfect match for any helmet mounted applications. The photoluminescent ("glow in the dark") shroud ensures you'll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325Z0 in the most severe weather conditions. All these features plus Peli's Lifetime Guarantee* make the 3325Z0 a great companion for your work.

- 3 AA Batteries (Included)
- Glow-in-the-dark shroud
- Tail switch for easy one-handed operation
- Ingress Protected IPX7
- ATEX Safety Certified Zone 0 (Cat. 1)
- Peli's legendary lifetime guarantee**
- **Where applicable by law




DIMENSIONS

Length	6.06" (15.4 cm)
---------------	-----------------

MATERIALS

Body	Anti-static PC/PBT
O-Ring	EPDM
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static photo luminescent Polycarbonate (PC)

COLOURS

 High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Batteries Included	yes
Volts	4.5v

WEIGHT

Weight With Batteries	6.1 oz (173 gr)
------------------------------	-----------------

Weight Without Batteries

3.6 oz (102 gr) **Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

SWITCH

Document created on 02-13-20






Switch Type Push Button
Light Modes On / Off

CERTIFICATIONS

ATEX Zone 0

OTHER

Minimum Pack 1
Package Code C

FL1 STANDARD	HIGH
	155 LUMENS
	16h 0mins
	140m
	4926cd
	IPX7

ACCESSORIES