

Technische fiche / Fiche technique / Technical sheet

Universe	Professional
Type	Verticality
Category	Pulleys
Subcategory	Prusik pulleys



TWIN

High-strength double pulley designed for rescue professionals to set up progress capture systems of high mechanical advantage.

V3 10/10/2016
1 / 3

Short Description High strength, very high efficiency double Prusik pulley

Selling Points

- Special side plates designed for use with a Prusik friction hitch in progress capture systems
- Parallel mounted sheaves and auxiliary attachment point for creating different types of hauling systems, including the most complex
- Large diameter sheaves mounted on sealed ball bearings for excellent efficiency
- Accepts up to three carabiners to facilitate use

Specification

- Rope compatibility: 7 to 13 mm
- Sheave diameter: 51mm
- Ball bearings: yes
- Efficiency: 97%
- Maximum working load: $2 \times 3 \text{ kN} \times 2 = 12\text{kN}$
- Weight: 450g
- Certification(s): CE EN 12278, NFPA 1983 General Use

Specifications by reference

Reference(s)	P65A
Made in	FR
Guarantee	3 years
Packing	1
Case quantity	10
EAN	3342540087750

Related product(s) OK
 I'D L
 PAW
 GRIP 12.5 mm
 MICRO TRAXION