Technische fiche / Fiche technique / Technical sheet

| Universe | Professional |
|-------------|----------------|
| Туре | Verticality |
| Category | Pulleys |
| Subcategory | Prusik pulleys |





GEMINI

Compact double pulley for setting up progress capture systems of high mechanical advantage.

V2 10/10/2016 1 / 3

| Short Description | High efficiency, lightweight double Prusik pulley Special side plates designed for use with a Prusik friction hitch in progress capture systems Parallel mounted sheaves and auxiliary attachment point for creating different types of hauling systems Sheave mounted on sealed ball bearings for excellent efficiency Compact and lightweight | |
|-------------------|--|--|
| Selling Points | | |
| Specification | Rope compatibility: 7 to 11 mm Sheave diameter: 25mm Ball bearings: yes Efficiency: 91% Maximum working load: 2 x 1,5 kN x 2 = 6kN Weight: 135g Certification(s): CE EN 12278, NFPA 1983 Technical Use | |

Specifications by reference

| Reference(s) | P66A |
|---------------|---------------|
| Made in | FR |
| Guarantee | 3 years |
| Packing | 1 |
| Case quantity | 8 |
| EAN | 3342540087743 |

Related product(s)

OK I'D S PAW AXIS 11 mm MICRO TRAXION