

**uvex**

**SAFETY EYEWEAR**

09.02.2010  
SBU-H-PGM-H-PM

skyguard NT 9175 260



<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* An improved spectacle with all-round protection</li><li>* An injection moulded TPU frame increase wearer protection levels through minimising the risk of particle ingress</li><li>* The flexible, closed-pore soft components enables a customised, individual fit</li><li>* Easy to clean to promote long term use</li><li>* Comfortable, customized fit by individual side arm inclination and length adjustment</li></ul>
<b>Technical details</b>	
<b>Frame</b>	
<b>Material</b>	<b>Front piece</b>
<b>Colour</b>	PP
	blue
<b>Material</b>	<b>TPU layer</b>
<b>Colour</b>	TPU
	grey

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Material</b>	<b>Side piece</b> PBT+PC
<b>Features</b>	adjustable inclination
<b>Colour</b>	blue
<b>Material</b>	<b>Temple</b> PP
<b>Features</b>	adjustable to four different lengths
<b>Colour</b>	blue
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificat. body	0196
<b>Lens</b>	
<b>Material</b>	PC
<b>Thickness</b>	2,1 mm
<b>Coating</b>	supravision HC-AF
<b>Colour</b>	clear

<b>Filter</b>	<b>Marking</b>
Manufacturer's ID code	2-1,2 ( DIN EN 170)
Optical class	W
Low-energy impact	1
Surface resistance to fine particles	F (45 m/s)
Antifog	K
Tested acc. to DIN	N
Conformity symbol	DIN
	CE
<b>Miscellaneous</b>	
Weight	42 g
Packing	5 spectacles
	160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170